



JAPAN'S NO.1 TRACTOR COMPANY

MU

MU5501

PERFORMANCE • EFFICIENCY • RELIABILITY



E-CDIS Engine



4 Valves System



Planetary Drive



Shuttle Shift

*terms & conditions apply

SPECIFICATIONS

Model		MU5501-2WD
Engine	Type	Kubota V2403-M-DI-T, Inline FIP E-CDIS, 4 Cylinder, Liquid Cooled
	Hourse Power	55 HP@ 2300 Rated ERPM
	Displacement	2434 cc
	Backup Torque	27%
Transmission	Air Filter	Dry Type, Dual Element
	Clutch	Double Clutch
	Gear Box	8 Forward + 4 Reverse Main Transmission Synchronesh
Brakes	Speeds	Forward Min 3 - Max 31 kmph Reverse Min 5 - Max 13 kmph
	Type	Oil Immersed Disc Brakes
Final Reduction	Type	Planetary
Front Axle	Type	Variable 2WD
Hydraulics	Lifting Capacity	1,800 kgf and 2,100 kgf (at lift point)
Steering	Type	Power (Hydraulic Double acting)
Power Take Off	Type	Independent, Dual PTO/Rev. PTO (Optional)
PTO RPM		STD : 540 @2300 ERPM
		ECO : 750 @2200 ERPM
		RPTO: 540R @2150 ERPM (Optional)
Wheels & Tyres	Front	7.5 x 16
	Rear	16.9 x 28
Electrical System	Battery	12 Volt
	Alternator	40 Amp
	Starter Motor	12 Volt, 2.2 kW
Dimensions & Weight	Total Weight	2200 Kg
	Wheel Base	2100 mm
	Overall Length (without 3P)	3250 mm
	Overall Width	1850 mm
	Ground Clearance	415 mm
Others	Turning Radius with Brakes	2850 mm
	Deck Design	Full flat
	Fuel Tank Capacity	65 Liters
Factory Fitted Options		Auxiliary Control Valve

Calculated according to our criteria. The actual capacity you achieve may be different.
The specifications, information, and appearance of the machines herein are subject to change without notice.

WITH YOU AT EVERY TURN



Kubota Agricultural Machinery India Pvt. Ltd.

No.15, Medavakkam Road, Sholinganallur, Chennai - 600 119
Tamilnadu, India. Tel : +91 44 6104 1500 Fax : 044 6104 1600
Website : www.kubota.co.in

Toll Free : 1800 - 425 - 1694

KUBOTA / MARCH-19 / ENGLISH