



JAPAN'S NO.1 TRACTOR COMPANY

**MU**

**MU5501**

PERFORMANCE • EFFICIENCY • RELIABILITY



**4x4  
55HP**



**E-CDIS Engine**



**4 Valves System**



**Planetary Drive**



**Shuttle Shift**

\*Terms & conditions apply

**SPECIFICATIONS**

Model	Specification	MU5501-4WD
<b>Engine</b>	Type	Kubota V2403-M-DI-T, Inline FIP E-CDIS, 4 Cylinder, Liquid Cooled
	Horse Power	55 HP@ 2300 Rated ERPM
	Displacement	2434 cc
	Backup Torque	27%
	Air Filter	Dry Type, Dual Element
<b>Transmission</b>	Clutch	Double Clutch
	Gear Box	8 Forward + 4 Reverse Main Transmission Synchronesh
	Speeds	Forward 3 - 31 kmph Reverse 5 - 13 kmph
<b>Brakes</b>	Type	Oil Immersed Disc Brakes
<b>Final Reduction</b>	Type	Planetary
<b>Front Axle</b>	Type	Fixed Tread (4WD) *Bevel-Gear system (Benefit for water-proof)
<b>Hydraulics</b>	Lifting Capacity	1,800 kgf and 2,100 kgf (at lift point)
<b>Steering</b>	Type	Power (Hydraulic Double acting)
<b>Power Take Off</b>	Type	Independent, Dual PTO
	PTO RPM	STD : 540 @2300 ERPM, ECO : 750 @2200 ERPM
<b>Wheels &amp; Tyres</b>	Front	9.5 x 24
	Rear	16.9 x 28
<b>Electrical System</b>	Battery	12 Volt
	Alternator	40 Amp
	Starter Motor	12 Volt, 2.2 kW
<b>Dimensions &amp; Weight</b>	Total Weight	2380 Kg
	Wheel Base	2050 mm
	Overall Length (without 3P)	3250 mm
	Overall Width	1850 mm
	Ground Clearance	415 mm
<b>Other</b>	Turning Radius with Brakes	3.0 m
	Deck Design	Full flat
<b>Factory Fitted Options</b>	Fuel Tank Capacity	65 Liters
		Auxiliary Control Valve

Calculated according to our criteria. The actual capacity you achieve may be different. The specifications, information, and appearance of the machines herein are subject to change without notice.

**WITH YOU AT EVERY TURN**



KUBOTAMARCH-19/ENGLISH

**Kubota Agricultural Machinery India Pvt Ltd.**  
 #15, Medavakkam Road, Sholinganallur,  
 Chennai-600119, Tamilnadu, India  
 Tel : +91 - 44 - 6104 1500 Fax : 044 6104 1600  
 Web : www.kubota.co.in



**Toll Free : 1800 - 425 - 1694**